

Serial No.: 10/086,569

Filing Date: 2/28/2002

Attorney Docket No. 100.316US01

Title: RESILIENT DETECTION OF REPEATERS

---

**Amendments to the Claims:**

Claims 1, 6-13, 19-26, 30-35, 37-40, 43-49, 51-53 and 57-59 have been amended. No new matter has been added.

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of claims:**

1. (Currently Amended) A communication device, comprising:

at least one communication interface;

a communication interface circuit coupled to the at least one communication interface,

wherein the communication interface circuit communicates using a communication protocol, wherein the communication protocol contains an embedded operation channel (EOC) and a hop count;

wherein the communication interface circuit is adapted to send a discovery query and to receive discovery response messages over the EOC of the at least one communication interface; and

wherein the communication interface circuit is adapted to compare a hop count from a discovery response message from a second communication device to a total number of ~~received~~ discovery response messages received from the second communication device and any intervening communication devices.

Serial No.: 10/086,569

Filing Date: 2/28/2002

Attorney Docket No. 100.316US01

Title: RESILIENT DETECTION OF REPEATERS

---

2. (Original) The communication device of claim 1, wherein the communication device is a doubler.
3. (Original) The communication device of claim 1, wherein the communication device is a terminal communication device.
4. (Original) The communication device of claim 1, wherein the communication device is a Global Symmetric High-speed Digital Subscriber Line (G.SHDSL) communication device.
5. (Original) The communication device of claim 1, wherein the communication device is adapted to selectively configure the communication interface circuit and the at least one communication interface in response to the received discovery response messages.
6. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to send atthe discovery query and to receive discovery response messages over the EOC of a plurality of communication interfaces simultaneously.

7. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication interface upon initialization of the communication device.
8. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication interface upon having the at least one communication interface coupled to an active communication link.
9. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication interface upon receipt of a manual discovery request from a system operator.
10. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to resend atthe discovery query if the total number of ~~received~~ discovery response messages received does not match the hop count from the discovery response message from the second communication device.

11. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to resend atthe discovery query if no discovery response messages is received from the second communication device.
12. (Currently Amended) The communication device of claim 1, wherein the communication interface circuit is adapted to resend atthe discovery query if the number of received discovery response messages does not match the hop count from the discovery response message from the ~~far-end~~second communication device after a selected waiting period from the time the discovery response message from the ~~far-end~~second communication device was received.
13. (Currently Amended) A communication system, comprising:
- a communication link;
- a plurality of communication devices coupled to the communication link, wherein at least two communication devices of the plurality of communication devices are terminal communication devices, and wherein at least one of the plurality of communication devices comprises:
- at least one communication interface coupled to the communication link;
- a communication interface circuit coupled to the at least one communication interface, wherein the at least one communication interface circuit communicates

using a communication protocol, wherein the communication protocol contains an embedded operation channel (EOC) and a hop count;

wherein the communication interface circuit is adapted to send a discovery query to the plurality of communication devices coupled to the communication link and receive discovery response messages over the EOC from the plurality of communication devices; and

wherein the communication interface circuit is adapted to compare a hop count from the discovery response message from one of the at least two terminal communication devices coupled to the communication link to a total number of ~~received~~ discovery response messages received from the one of the at least two terminal communication devices and any intervening communication devices of the plurality of communication devices.

14. (Original) The communication system of claim 13, wherein the at least one communication device is a doubler.
15. (Original) The communication system of claim 13, the at least one communication device is a terminal communication device.

16. (Original) The communication system of claim 13, wherein the communication system is a High-speed Digital Subscriber Line (HDSL) communication system.
17. (Original) The communication system of claim 13, wherein the communication system is a Global Symmetric High-speed Digital Subscriber Line (G.SHDSL) communication system.
18. (Original) The communication system of claim 13, wherein the at least one communication device is adapted to selectively configure the communication interface circuit and the at least one communication interface in response to the received discovery response messages.
19. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to send atthe discovery query and to receive discovery response messages over the EOC of a plurality of communication interfaces simultaneously.
20. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit is adapted to send atthe discovery query and to receive

discovery response messages over the at least one communication interface upon initialization of the at least one communication device.

21. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication interface upon having the at least one communication interface coupled to the communication link.
22. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication interface upon receipt of a manual discovery request from a system operator.
23. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to resend atthe discovery query if the number of received discovery response messages does not match the hop count from the discovery response message from one of the at least two terminal communication devices of the communication system.

24. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to resend at the discovery query if no discovery response messages is received from one of the at least two terminal communication devices of the communication system.
25. (Currently Amended) The communication system of claim 13, wherein the communication interface circuit of the at least one communication device is adapted to resend at the discovery query when the number of received discovery response messages does not match the hop count ~~from the discovery response message from the far-end communication device of the communication system~~ after a selected waiting period from the time the discovery response message from one of the at least two terminal communication devices was received.
26. (Currently Amended) A High-speed Digital Subscriber Line (HDSL) communication device, comprising:
- at least one HDSL communication interface;
- an HDSL communication circuit coupled to the at least one HDSL communication interface, wherein the HDSL communication circuit communicates using HDSL



communication protocol containing an embedded operation channel (EOC) and a hop count;

wherein the HDSL communication circuit is adapted to send an HDSL discovery query and to receive HDSL discovery response messages over the EOC through the at least one HDSL communication interface; and

wherein the HDSL communication circuit is adapted to compare a hop count from an HDSL discovery response message from a second HDSL communication device to a total number of received HDSL discovery response messages received from the second HDSL communication device and any intervening HDSL communication devices.

27. (Original) The HDSL communication device of claim 26, wherein the HDSL communication device further comprises:

a processor coupled to the HDSL communication circuit; and

a machine-usable storage media coupled to the processor, wherein the processor utilizes discovery firmware stored on the machine-usable storage media to conduct discovery on the HDSL communication interface.

28. (Original) The HDSL communication device of claim 26, wherein the HDSL communication device is an HDSL doubler.
29. (Original) The HDSL communication device of claim 26, wherein the HDSL communication device is a terminal HDSL communication device.
30. (Currently Amended) The HDSL communication device of claim 26, wherein the HDSL communication circuit is adapted to send atthe discovery query and to receive discovery response messages over the EOC of a plurality HDSL communication interfaces simultaneously.
31. (Currently Amended) The HDSL communication device of claim 26, wherein the HDSL communication circuit is adapted to send atthe discovery query and to receive discovery response messages over the at least one communication HDSL interface upon initialization of the HDSL communication device.
32. (Currently Amended) The HDSL communication device of claim 26, wherein the HDSL communication circuit is adapted to send atthe discovery query and to receive discovery response messages over the at least one HDSL communication interface upon having the

at least one HDSL communication interface coupled to an active HDSL communication link.

33. (Currently Amended) The HDSL communication device of claim 26, wherein the HDSL communication circuit is adapted to resend ~~at~~the discovery query when the total number of ~~received~~ discovery response messages received does not match the hop count from the discovery response message from the ~~far-end~~second HDSL communication device.
34. (Currently Amended) The HDSL communication device of claim 26, wherein the HDSL communication circuit is adapted to resend ~~at~~the discovery query when no discovery response messages are received from the ~~far-end~~second HDSL communication device.
35. (Currently Amended) A High-speed Digital Subscriber Line (HDSL) communication system, comprising:
- an HDSL communication link; and
- a plurality of HDSL communication devices coupled to the HDSL communication link, wherein at least two HDSL communication devices of the plurality of HDSL communication devices are terminal HDSL communication devices, and wherein at least one of the plurality of HDSL communication devices comprises:

at least one HDSL communication interface coupled to the HDSL communication link;

an HDSL communication interface circuit coupled to the at least one HDSL communication interface, wherein the at least one HDSL communication interface circuit communicates using an HDSL communication protocol, wherein the HDSL communication protocol contains an embedded operation channel (EOC) and a hop count;

wherein the HDSL communication interface circuit is adapted to send a discovery query to the plurality of HDSL communication devices coupled to the HDSL communication link and receive discovery response messages over the EOC from the plurality of HDSL communication devices; and

wherein the HDSL communication interface circuit is adapted to compare a hop count from the discovery response message from one of the at least two terminal HDSL communication devices coupled to the HDSL communication link to a total number of ~~received~~ discovery response messages received from the one of the at least two terminal HDSL communication devices and any intervening HDSL communication devices of the plurality of HDSL communication devices.

36. (Original) The HDSL communication system of claim 35, wherein the HDSL communication interface circuit is adapted to send a discovery query and to receive

discovery response messages over the at least one HDSL communication interface upon initialization of the at least one HDSL communication device.

37. (Currently Amended) The HDSL communication system of claim 35, wherein the HDSL communication interface circuit of the at least one HDSL communication device is adapted to send atthe discovery query and to receive discovery response messages over the at least one HDSL communication interface when the at least one HDSL communication interface coupled to the HDSL communication link.
38. (Currently Amended) The HDSL communication system of claim 35, wherein the HDSL communication interface circuit of the at least one HDSL communication device is adapted to resend atthe discovery query if the number of received discovery response messages does not match the hop count from the discovery response message from one of the at least two terminal HDSL communication devices of the HDSL communication system.
39. (Currently Amended) The HDSL communication system of claim 35, wherein the HDSL communication interface circuit of the at least one HDSL communication device is adapted to resend atthe discovery query if no discovery response messages is received from one of the at least two terminal HDSL communication devices of the communication system.

40. (Currently Amended) A method of operating a communication device, comprising:
- sending a discovery ~~query~~request on an embedded operation channel (EOC);
- receiving ~~at least one~~ discovery response messages from at least one other terminal  
communication device and any intervening communication devices, wherein at least  
~~one response message of the at least one discovery response message is a discovery~~  
~~response from a terminal communication device~~;
- extracting a hop count from ~~the~~a discovery response message from the terminal  
communication device; and
- comparing ~~the~~a total number of discovery response messages received from the terminal  
communication device and any intervening communication devices to a hop count of  
the discovery response message from the terminal communication device to  
determine if discovery is complete.
41. (Original) The method of claim 40, further comprising:
- storing discovery routines on a machine readable storage medium.
42. (Original) The method of claim 40, further comprising:

selectively configuring the communication device in response to the received at least one discovery response messages.

43. (Currently Amended) The method of claim 40, wherein sending athe discovery query and receiving ~~at least one~~ discovery response messages further comprises sending athe discovery query and receiving ~~at least one~~ discovery response messages upon initialization of the communication device.
44. (Currently Amended) The method of claim 40, wherein sending athe discovery query and receiving ~~at least one~~ discovery response messages further comprises sending athe discovery query and receiving ~~at least one~~ discovery response messages upon coupling the communication device to a communication link.
45. (Currently Amended) The method of claim 40, wherein sending athe discovery query and receiving ~~at least one~~ discovery response messages further comprises sending athe discovery query and receiving ~~a~~~~at least one~~ discovery response messages upon receipt of a manual discovery request from a system operator.
46. (Currently Amended) The method of claim 40, further comprising:

resending atthe discovery query when the number of received discovery response messages does not match the hop count of the discovery response message from the terminal communication device.

47. (Currently Amended) The method of claim 40, further comprising:

resending atthe discovery query if no discovery response messages are received from the terminal communication device.

48. (Currently Amended) The method of claim 40, further comprising:

resending atthe discovery query if the number of received discovery response messages does not match the hop count of the discovery response message from the terminal communication device after a selected waiting period from the time the discovery response message from the terminal communication device was received.

49. (Currently Amended) A method of operating a communications system, comprising:

transmitting a discovery query~~request~~ from a first communication device on an embedded operation channel (EOC);

receiving ~~at least one~~ discovery response messages from the at least one second terminal communication device and any intervening communication devices, wherein at least



~~one response message of the at least one discovery response message is a discovery response from a terminal communication device;~~

extracting a hop count from ~~the~~ discovery response from the at least one terminal communication device; and

determining if discovery is complete by comparing ~~the~~ total number of discovery response messages received from the terminal communication device and any intervening communication devices to ~~the~~ hop count from the discovery response message ~~offrom~~ the at least one terminal communication device.

50. (Original) The method of claim 49, further comprising:

selectively configuring the first communication device in response to the received ~~at least one~~ discovery response messages.

51. (Currently Amended) The method of claim 49, wherein transmitting ~~at least one~~ discovery query and receiving ~~at least one~~ discovery response messages further comprises transmitting a discovery query and receiving at least one discovery response message upon initialization of the first communication device.

52. (Currently Amended) The method of claim 49, wherein transmitting ~~at least one~~ discovery query and receiving ~~at least one~~ discovery response messages further comprises transmitting

a discovery query and receiving at least one discovery response message upon coupling the first communication device to a communication link.

53. (Currently Amended) The method of claim 49, wherein transmitting a discovery query and receiving ~~least one~~ discovery response messages further comprises transmitting a discovery query and receiving at least one discovery response message upon receipt of a manual discovery request from a system operator.

54. (Original) The method of claim 49, further comprising:  
  
re-transmitting a discovery query when the number of received discovery response messages does not match the hop count from the discovery response message from the terminal communication device.

55. (Original) The method of claim 49, further comprising:  
  
re-transmitting a discovery query when no discovery response messages are received from the terminal communication device.

56. (Original) The method of claim 49, further comprising:

re-transmitting a discovery query when the number of received discovery response messages does not match the hop count from the discovery response message from the terminal communication device after a selected waiting period from the time the discovery response message from the terminal communication device was received.

57. (Currently Amended) A method of operating a High-speed Digital Subscriber Line (HDSL) communication device, comprising:

sending a discovery request on an embedded operation channel (EOC) of an HDSL communication link coupled to the HDSL communication device;

receiving ~~at least one~~ discovery response messages ~~from the at least one other terminal~~ HDSL communication device and any intervening HDSL communication devices coupled to the HDSL communication link, ~~wherein at least one response message of the at least one discovery response messages is a discovery response from a terminal~~ HDSL communication device of the HDSL communication link; and

comparing ~~the a total~~ number of discovery response messages received from the terminal HDSL communication device and any intervening HDSL communication devices to a hop count from ~~the a~~ discovery response message from the terminal HDSL communication device to determine if discovery is complete.

58. (Currently Amended) A method of operating a High-speed Digital Subscriber Line

(HDSL) communication system, comprising:

transmitting a discovery request from a first HDSL communication device on an

embedded operation channel (EOC) of an HDSL communication link coupled to the

first HDSL communication device and at least one second HDSL communication

device;

receiving at least one discovery response message from the at least one second HDSL

communication device, wherein at least one response message of the at least one

discovery response messages is a discovery response from a terminal HDSL

communication device of the HDSL communication link; and

determining if discovery is complete by comparing ~~thea total~~ number of discovery

response messages received from the terminal HDSL communication device and any

intervening HDSL communication devices coupled to the HDSL communication link

to a hop count from the discovery response message from the ~~HDSL-terminal~~ HDSL

communication device.

59. (Currently Amended) A machine-usable medium having machine-readable instructions

stored thereon for execution by a processor of a communication device to perform a

method comprising:

sending a discovery request on an embedded operation channel (EOC) of a

communication link coupled to the communication device;

receiving ~~at least one~~ discovery response messages from at least one ~~other~~ terminal communication device and any intervening communication devices coupled to the communication link, ~~wherein at least one response message of the at least one~~ discovery response messages is a discovery response from a terminal communication device ~~of the communication link~~; and

comparing ~~the a total~~ number of discovery response messages received from the terminal communication device and any intervening communication devices coupled to the communication link to a hop count from the discovery response message from the terminal communication device to determine if discovery is complete.